


Female Header

pitch 2.54mm (0.1") | Single row | Dip | Boder spacer

CSHA102
CSHA136
CSHA138 Series



Specifications


Current Rating :	3.0 Ampere
Insulation Resistance :	1000 MΩ Min
Dielectric Withstanding :	600V AC
Contact Resistance :	20 mΩ Max
Operating Temperature :	-40°C to +105°C

Materials


Contact Material :	Phosphor Bronze
Insulation Material :	High Temperature Thermoplastic, 94V-0 Nylon

All materials must meet Greenconn's requirements for environmental protection.

Mating with



P.S. : Suggested mating pin length : 4.0 ~ 6.0 mm



* For Coded Dimension Not Inside The Table, Please Refer To "Ordering Information"

No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information		
	C	D	E		C	D	E		C	D	E		C	D	E
02	2.54	5.58	5.08	11	25.40	28.44	27.94	21	50.80	53.84	53.34	31	76.20	79.24	78.74
03	5.08	8.12	7.62	12	27.94	30.98	30.48	22	53.34	56.38	55.88	32	78.74	81.78	81.28
04	7.62	10.66	10.16	13	30.48	33.52	33.02	23	55.88	58.92	58.42	33	81.28	84.32	83.82
05	10.16	13.20	12.70	14	33.02	36.06	35.56	24	58.42	61.46	60.96	34	83.82	86.86	86.36
06	12.70	15.74	15.24	15	35.56	38.60	38.10	25	60.96	64.00	63.50	35	86.36	89.40	88.90
07	15.24	18.28	17.78	16	38.10	41.14	40.64	26	63.50	66.54	66.04	36	88.90	91.94	91.44
08	17.78	20.82	20.32	17	40.64	43.68	43.18	27	66.04	69.08	68.58	37	91.44	94.48	93.98
09	20.32	23.36	22.86	18	43.18	46.22	45.72	28	68.58	71.62	71.12	38	93.98	97.02	96.52
10	22.86	25.90	25.40	19	45.72	48.76	48.26	29	71.12	74.16	73.66	39	96.52	99.56	99.06
				20	48.26	51.30	50.80	30	73.66	76.70	76.20	40	99.06	102.10	101.60

Ordering Information

CSHA1	XX	-	XX	XX	X	XXX	R1AA
	Height Option (H)		No. of Pins per Row	Standard Plating		Pin Length (B)	
	02 : H=11.04		02	02 : Gold Flash	CSHA102...A	002 : B=2.30 (1 Stacker)	
	36 : H=16.12		38		CSHA136...A	003 : B=2.30 (3 Stackers)	
	38 : H=21.20		40	Selective Plating	CSHA138...A	001 : B=2.30 (5 Stackers)	
				01 : Tin			For special length requirement Please contact our sales personnel
				05 : Gold Flash / Tin			

Standard Packaging : Box