


Specifications

Current Rating :	2.0 Ampere
Insulation Resistance :	1000 MΩ Min
Dielectric Withstanding :	500V AC
Contact Resistance :	20 mΩ Max
Operating Temperature :	-40°C to +105°C





Materials


Contact Material : Phosphor Bronze
Insulation Material : High Temperature Thermoplastic, 94V-0 LCP

All materials must meet Greenconn's requirements for environmental protection.





Mating with



D50



D51



* For Coded Dimension Not Inside The Table, Please Refer To "Ordering Information"

No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information		
	C	D			C	D			C	D			C	D	
				11	20.00	22.00		21	40.00	42.00		31	60.00	62.00	
02	2.00	4.00		12	22.00	24.00		22	42.00	44.00		32	62.00	64.00	
03	4.00	6.00		13	24.00	26.00		23	44.00	46.00		33	64.00	66.00	
04	6.00	8.00		14	26.00	28.00		24	46.00	48.00		34	66.00	68.00	
05	8.00	10.00		15	28.00	30.00		25	48.00	50.00		35	68.00	70.00	
06	10.00	12.00		16	30.00	32.00		26	50.00	52.00		36	70.00	72.00	
07	12.00	14.00		17	32.00	34.00		27	52.00	54.00		37	72.00	74.00	
08	14.00	16.00		18	34.00	36.00		28	54.00	56.00		38	74.00	76.00	
09	16.00	18.00		19	36.00	38.00		29	56.00	58.00		39	76.00	78.00	
10	18.00	20.00		20	38.00	40.00		30	58.00	60.00		40	78.00	80.00	

Ordering Information

GPFB3

XX

Height Option (H)

01

☐ XX

No. of Pins per Row

02

2

40

XX

Standard Plating

02 : Gold Flash

Selective Plating

01 : Tin

05 : Gold Flash / Tin

Standard Packaging : Tube

☒

XXX

A

Pin Length (A/B/E)

001 : A=3.20 / B=2.60 / E=1.27

002 : A=4.00 / B=2.55 / E=1.27

For special length requirement
Please contact our sales personnel

C1BC