

Pin Header

pitch 2.54mm (0.1") | Dual row | Dip

GPHA212 Series


Specifications

Current Rating :	3.0 Ampere
Insulation Resistance :	1000 MΩ Min
Dielectric Withstanding :	600V AC
Contact Resistance :	20 mΩ Max
Operating Temperature :	-40°C to +105°C






Materials

Contact Material :	Brass
Insulation Material :	High Temperature Thermoplastic, 94V-0 PBT

All materials must meet Greenconn's requirements for environmental protection.



Mating with



* For Coded Dimension Not Inside The Table, Please Refer To "Ordering Information"

No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information		
	C	D			C	D			C	D			C	D	
				11	25.40	27.94		21	50.80	53.34		31	76.20	78.74	
				12	27.94	30.48		22	53.34	55.88		32	78.74	81.28	
				13	30.48	33.02		23	55.88	58.42		33	81.28	83.82	
04	7.62	10.16		14	33.02	35.56		24	58.42	60.96		34	83.82	86.36	
05	10.16	12.70		15	35.56	38.10		25	60.96	63.50		35	86.36	88.90	
06	12.70	15.24		16	38.10	40.64		26	63.50	66.04		36	88.90	91.44	
07	15.24	17.78		17	40.64	43.18		27	66.04	68.58		37	91.44	93.98	
08	17.78	20.32		18	43.18	45.72		28	68.58	71.12		38	93.98	96.52	
09	20.32	22.86		19	45.72	48.26		29	71.12	73.66		39	96.52	99.06	
10	22.86	25.40		20	48.26	50.80		30	73.66	76.20		40	99.06	101.60	

Ordering Information

GPHA2	XX	-	XX	XX	XX	X	XXX	A1BA
	Height Option (H)		No. of Pins per Row	Standard Plating		A	Pin Length (A / B)	
	12		04	02 : Gold Flash			001 : A=6.00 / B=3.00	
			40	Selective Plating			003 : A=7.00 / B=3.00	
				01 : Tin			For special length requirement	
				05 : Gold Flash / Tin			Please contact our sales personnel	