

Pin Header

pitch 2.54mm (0.1") | Dual row | Dip

GPHA213 Series


Specifications

Current Rating :	3.0 Ampere
Insulation Resistance :	1000 MΩ Min
Dielectric Withstanding :	600V AC
Contact Resistance :	20 mΩ Max
Operating Temperature :	-40°C to +105°C





Materials

Contact Material :	Brass
Insulation Material :	High Temperature Thermoplastic, 94V-0 LCP

All materials must meet Greenconn's requirements for environmental protection.



Mating with



* For Coded Dimension Not Inside The Table, Please Refer To "Ordering Information"

No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information		
	C	D			C	D			C	D	
				11	25.40	27.82		21	50.80	53.22	
02	2.54	4.96		12	27.94	30.36		22	53.34	55.76	
03	5.08	7.50		13	30.48	32.90		23	55.88	58.30	
04	7.62	10.04		14	33.02	35.44		24	58.42	60.84	
05	10.16	12.58		15	35.56	37.98		25	60.96	63.38	
06	12.70	15.12		16	38.10	40.52		26	63.50	65.92	
07	15.24	17.66		17	40.64	43.06		27	66.04	68.46	
08	17.78	20.20		18	43.18	45.60		28	68.58	71.00	
09	20.32	22.74		19	45.72	48.14		29	71.12	73.54	
10	22.86	25.28		20	48.26	50.68		30	73.66	76.08	

Ordering Information

GPHA2

XX

Height Option (H)

13

- XX

No. of Pins per Row

02

3

30

XX

Standard Plating

02 : Gold Flash

Selective Plating

01 : Tin

05 : Gold Flash / Tin

Standard Packaging : Box

X

A

XXX

Pin Length (A / B)

001 : A=6.00 / B=3.00

005 : A=4.95 / B=3.45

For special length requirement
Please contact our sales personnel

C1BA