

INKJET CODE Description : XX X XX XX

XX-YEAR: 20 = 2020
X-MONTH: A = JAN, B = FEB,.....
XX-DAY: 14 = 14th DAY
XX-HOUR: 14 = 14 PM




Specifications

Current Rating 14 AWG: 13.0Amp AC/DC
16 AWG: 13.0Amp AC/DC
18 AWG: 10.0Amp AC/DC
20 AWG: 7.5Amp AC/DC




Voltage Rating: 250V AC/DC.
Insulation Resistance:1000MΩMin.
Dielectric Withstanding Voltage:1500VAC
Contact Resistance:20mΩMax.
Operating Temperature:-55°C to +125°C

Materials
Insulator Material:High Temperature
Thermoplastic, UL 94V-0 PA66
or the equivalent material

☆ All materials must meet Greenconn
hazardous substances control standards.
★: Critical Characteristics.
indicates product characteristics,
functionalities, and manufacturing processes
regarding to customer's specifications
★: Safety Features
indicates product characteristics,
functionalities, and manufacturing processes
complying to legal regulations stated by
local government




INKJET CODE



Website:www.greenconn.com
E-mail:sales@greenconn.com

REV. 01 UNIT. mm SCALE. 3:2

3RD.ANG
PROJ.



PAGE. 1/1

GENERAL TOLERANCE

X.±3.0'	X.±0.30
.X'±2.0'	.X±0.25
.XX'±1.0'	.XX±0.20
.XXX'±0.5'	.XXX±0.15

DESIGNED:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

DWG. NO.

AGZ081-HA-N

PART NO.

AGZ081-02APA-N

TITLE.

2 WAY PLUG
STANDARD SEAL
GT SERIES