



Specifications
 Current Rating 20 AWG: 3.5Amp/PIN
 22 AWG: 3.0Amp/PIN
 24 AWG: 2.0Amp/PIN
 26 AWG: 1.0Amp/PIN
 Voltage Rating: 250V AC/DC.
 Insulation Resistance:1000MΩMin.
 Dielectric Withstanding Voltage:650VAC
 Contact Resistance:30mΩMax.
 Operating Temperature:-40°C to +105°C
Materials
 Insulator Material:Temperature
 Thermoplastic, UL 94V-0 PBT
 or the equivalent material
 ★ All materials must meet Greenconn
 hazardous substances control standards.
 ★★: Critical Characteristics.
 indicates product characteristics,
 functionalities, and manufacturing processes
 regarding to customer's specifications
 ★★: Safety Features
 indicates product characteristics,
 functionalities, and manufacturing processes
 complying to legal regulations stated by
 local government



REV. C UNIT. mm SCALE. 3:2

3RD.ANG
PROJ.
PAGE. 1/1

GENERAL TOLERANCE	
X.'±3.0'	X.±0.30
.X'±2.0'	.X±0.25
.XX'±1.0'	.XX±0.20
.XXX'±0.5'	.XXX±0.15

DESIGNED:
CHECKED:
APPROVED:

DATE:
DATE:
DATE:

DWG. NO.
AHW062-HA
PART NO.
AHW062-03AAT-N

TITLE.
2.2Pitch 6Pin SEAL Series
Female Ass'y