



适用线路板
RECOMMENDED PCB LAYOUT



SECTION A-A

NOTES

RATING
OPERATING TEMPERATURE: -25~85°C
OPERATING VOLTAGE: 50V AC/DC
CURRENT RATING: 0.5 AMPS
DIELECTRIC WITHSTANDING VOLTAGE:
500V AC/Minute;
INSULATION RESISTANCE: 500MΩ Min;
CONTACT RESISTANCE: 0.03Ω Max;

MATERIAL;
Contact Material: Phosphor Bronze
Insulator Material: LCP UL94V-0

Ordering Information


C FCB105 - XX XX A 004 C X A X -06
No. of Pins per Row 30
Selective Plating 01=Tin
Selective Plating 02=Gold Flash
Color 1=Black 2=White
Standard Packing C=Tube
Selective Packing B=Tray



Website: www.greenconn.com
E-mail: sales@greenconn.com

REV. A UNIT. mm SCALE. 1:1

3RD ANG
PROJ.



PAGE. 1/1

GENERAL TOLERANCE

X'±5.0'	X±0.35
.X'±3.0'	.X±0.30
.XX'±2.0'	.XX±0.25
.XXX'±1.0'	.XXX±0.10

DESIGNED:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

DWG. NO.

CFCB105-CA004

PART NO.

CFCB105-30XX A004CXAX-06

TITLE.

1.0 FPC CONN. NON ZIF DIP FRONTFLIP H=3.5 CONTACT