



適用FPC寸法
Applicable FPC

Specifications

Voltage Rating:50V AC/DC

Contact Resistance:30 mΩ Max

Insulation Resistance: 500M Ω Min.

Dielectric Withstanding Voltage: 500V,AC/Minute

Temperature Range: -25°C~+85°C

Materials

Contact: Phosphor Bronze

Insulation: High Temperature Thermoplastic
UL 94V-0 LCP or the equivalent material

Actuafor:LCP(UL94V-0)

All materials must meet Greenconn requirement for environment protection

Ordering Information

C FCD150 — XX XX A 042 C X A X

No. of Pins per Row
05,05,10,20,30

Selective Plating
01=Tin

Color
2=White

Standard Packing
C=Tube

Selective Packing
D=T&R

No. of Contact	Dimension Information		
	M	L1	L
04	3.00	5.10	11.00
05	4.00	6.10	12.00
06	5.00	7.10	13.00
07	6.00	8.10	14.00
08	7.00	9.10	15.00
09	8.00	10.10	16.00
10	9.00	11.10	17.00
11	10.00	12.10	18.00
12	11.00	13.10	19.00
13	12.00	14.10	20.00
14	13.00	15.10	21.00
15	14.00	16.10	22.00
16	15.00	17.10	23.00
17	16.00	18.10	24.00
18	17.00	19.10	25.00
19	18.00	20.10	26.00
20	19.00	21.10	27.00
21	20.00	22.10	28.00
22	21.00	23.10	29.00
23	22.00	24.10	30.00
24	23.00	25.10	31.00
25	24.00	26.10	32.00
26	25.00	27.10	33.00
27	26.00	28.10	34.00
28	27.00	29.10	35.00
29	28.00	30.10	36.00
30	29.00	31.10	37.00
31	30.00	32.10	38.00
32	31.00	33.10	39.00
40	39.00	41.10	47.00

格稜股份有限公司
Greenconn Corporation

GENERAL TOLERANCE	
X. $\pm$ 5.0'	X. $\pm$ 0.38
.X $\pm$ 3.0'	.X $\pm$ 0.30
.XX $\pm$ 2.0'	.XX $\pm$ 0.25
.XXX $\pm$ 1.0'	.XXX $\pm$ 0.20

DESIGN:	DATE:
CHECKED:	DATE:
AUDITED:	DATE:

DWG. NO.	CFCFD150-CA42CA
PART NO.	CFCFD150-XXXX A042CXAX

TITLE.

1.0mm Pitch FPC 振基