





Specifications
Current Rating:2.0Amp
Insulation Resistance:1000MΩMin.
Dielectric Withstanding Voltage:500VAC
Contact Resistance:20mΩMax.
Operating Temperature:−40°C to +105°C
Materials
Contact Material:Phosphor Bronze
Insulator Material:
PBT(Not resistant to high temperature),
Nylon(High temperature resistance),
LCP(High temperature resistance),
UL 94V−0
All materials must meet Greenconn
hazardous substances control standards.



Recommended P.C.Board Layout
(Tolerance: ± 0.05)



Ordering Information

CSFF101 - XX XX A XXX C

Plastic specifications
1=Single row
2=Dual row
3=Tripe row
4=Quadruple

Water code

Positioning column information
A=No locating post
B=Round post
C=Square post

Pin length
See the drawing

Plating code
01=Tin
02=Gold Flash
05=Gold Flash/Tin
22=Matte Tin

No. of Pins per Row
02~40

Insulator Material
A=PBT
R=Nylon(Halogen)

1 S X

Color
1=Black
2=White
3=Yellow
E=Beige

Packing code
A=Box
B=Tray
C=Tube
D=Tape&Reel

Contact Material
A/S/K/T=Phosphor Bronze

No. of PIN/ROW	Dimension Information	
	M	L
02	2.00	4.60
03	4.00	6.60
04	6.00	8.60
05	8.00	10.60
06	10.00	12.60
07	12.00	14.60
08	14.00	16.60
09	16.00	18.60
10	18.00	20.60
11	20.00	22.60
12	22.00	24.60
13	24.00	26.60
14	26.00	28.60
15	28.00	30.60
16	30.00	32.60
17	32.00	34.60
18	34.00	36.60
19	36.00	38.60
20	38.00	40.60
21	40.00	42.60
22	42.00	44.60
23	44.00	46.60
24	46.00	48.60
25	48.00	50.60
26	50.00	52.60
27	52.00	54.60
28	54.00	56.60
29	56.00	58.60
30	58.00	60.60
31	60.00	62.60
32	62.00	64.60
33	64.00	66.60
34	66.00	68.60
35	68.00	70.60
36	70.00	72.60
37	72.00	74.60
38	74.00	76.60
39	76.00	78.60
40	78.00	80.60

格稜股份有限公司
Greenconn Corporation

格稜股份有限公司 Greenconn Corporation					GENERAL TOLERANCE X.±5.0° X.±0.30		DESIGN: DATE:		DWG. NO. CSFF101-CXX		TITLE. 2.00 FEMALE HEADER SINGLE ROW DIP TYPE BASE 4.30H	
REV. 01 UNIT. mm SCALE. 5:1 PAGE. 1/1 					.X°±3.0° .X±0.25		CHECKED: DATE:		PART NO. CSFF101-XXXX AXXX C1SX			
					.XX°±2.0° .XX±0.15		AUDITED: DATE:					
					.XXX°±1.0° .XXX±0.10		APPROVED: DATE:					