




Specifications
Current Rating:3.0Amp
Insulation Resistance:1000MΩMin.
Dielectric Withstanding Voltage:600VAC
Contact Resistance:20mΩMax.
Operating Temperature:-40°C to +105°C
Materials
Contact Material:Phosphor Bronze
Insulator Material:
Nylon(High temperature resistance),
LCP(High temperature resistance),
UL 94V-0
All materials must meet Greenconn hazardous substances control standards.



Recommended P.C.Board Layout
(Tolerance:±0.05)



No. of PIN/ROW	Dimension Information	
	M	L
03	5.08	12.50
04	7.62	15.04
05	10.16	17.58
06	12.70	20.12
07	15.24	22.66
08	17.78	25.20
09	20.32	27.74
10	22.86	30.28
11	25.40	32.82
12	27.94	35.36
13	30.48	37.90
14	33.02	40.44
15	35.56	42.98
16	38.10	45.52
17	40.64	48.06
18	43.18	50.60
19	45.72	53.14
20	48.26	55.68
21	50.80	58.22
22	53.34	60.76
23	55.88	63.30
24	58.42	65.84
25	60.96	68.38
26	63.50	70.92
27	66.04	73.46
28	68.58	76.00
29	71.12	78.54
30	73.66	81.08
31	76.20	83.62
32	78.74	86.16
33	81.28	88.70
34	83.82	91.24
35	86.36	93.78
36	88.90	96.32

Ordering Information

C SHC217 - XX XX A XXX X

Plastic specifications
1=Single row
2=Dual row
3=Tripe row
4=Quadruple

Water code

Positioning column information
A=No locating post
B=Round post
C=Square post

Pin length
See the drawing

Insulator Material
R=Nylon(Halogen Free)
C=LCP

Color
1=Black
2=White
3=Yellow
E=Beige

Contact Material
A=Phosphor Bronze

Standard Packing
C=Tube
Selective Packing
A=Box
G=Acetate Tape+Tube
H=Acetate Tape+Tape&Reel

No. of Pins per Row
03~36

Plating code
01=Tin
02=Gold Flash
05=Gold Flash/Tin
22=Matte Tin

格稜股份有限公司
Greenconn Corporation

GENERAL TOLERANCE		DESIGNED:	DATE:	DWG. NO.	TITLE.
X: ±5.0°	X: ±0.30	CHECKED:	DATE:		
.X: ±3.0°	.X: ±0.25	CO SIGNED:	DATE:	PART NO.	CSHC217-Series
.XX: ±2.0°	.XX: ±0.15	APPROVED:	DATE:		
.XXX: ±1.0°	.XXX: ±0.10			CSHC217-Series	

REV.	UNIT.	SCALE.	PAGE.
01	mm	3:1	1/1

2.54 FEMALE HEADER
DUAL ROWS SMT TYPE
CONNECTOR