







Electrical:

- 1.Turn ratio:1~2: J1~J2=1CT:1CT(±2%).
3~6: J3~J6=1CT:1CT(±2%).
- 2.OCL: 350uH Min.at 100KHz 100mV 8mA DC.
- 3.Insertion Loss: -1.0 dB Max 1~100MHz.
- 4.Return loss: -20dB Min 1~10MHz;
-16dB Min 10~30MHz.
-12dB Min 30~60MHz.
-10dB Min 60~80MHz.
- 5.Cross talk: -40dB Min 1~30MHz;
-35dB Min 30~60MHz;
-30dB Min 60~100MHz;
- 6.CMR: -30dB Min 1~100MHz;
- 7.Hi-Pot:1500V AC & 2250V DC
6S 1mA PRI TO SEC

LED Specification

Standard LED Color	LED Wavelength	Foward(A)	Foward(V)
Green	568nm	20mA	1.85~2.45V
Yellow	585nm	20mA	1.7~2.2V



Website:www.greenconn.com
E-mail:sales@greenconn.com

REV. 01 UNIT. mm SCALE. 1:1

3RD.ANG
PROJ.

PAGE. 2/3

GENERAL TOLERANCE

X.停 5.0'	X.?.35
.X停 3.0'	.X?.30
.XX停 2.0'	.XX?.25
.XXX停 1.0'	.XXX?. 10

DESIGNED:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

DWG. NO.

CTEA203-CB1AS


PART NO.

CTEA203-08XXB001AXSX

TITLE.

RJ45 180° TAB-UP
1*1 100BASE

PROFILE OF WAVE SOLDER



A.Preheating B.Soldering C.Gradual Cooling
 Tip temperature: 260±5°C.
 Tip temperature time: 5Sec Max.
 Tip melting point of Sn96.5/Ag3/Cu0.5: 217°C.


Remarks: after wave soldering, the plastic positioning columns of the product which under the PCB will be slightly melted, but it won't affect its function.



Website: www.greenconn.com
 E-mail: sales@greenconn.com

REV. 01 UNIT. mm SCALE. 1:1

3RD.ANG
 PROJ.



PAGE. 3/3

GENERAL TOLERANCE

X. 5.0'	X. ? .35
.X. 3.0'	.X. ? .30
.XX. 2.0'	.XX. ? .25
.XXX. 1.0'	.XXX. ? .10

DESIGNED:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

DWG. NO.

CTEA203-CB1AS

PART NO.

CTEA203-08XXB001AXSX

TITLE.

RJ45 180° TAB-UP
 1*1 100BASE