



PCB LAYOUT(±0.05)

MATERIAL:
 HOUSING: PBT,UL94V-0,Gray
 TERMINAL: PHOSPHOR BRONZE
 MECHANICAL:
 DURABILITY: 750 CYCLES MIN,12.5MM/MINUTE.
 INSERTION FORCE: 2.2KG.F MAX
 RETENTION STRENGTH: 7.7KG.F BETWEEN JACK AND PLUG
 OPERATING TEMPERATURE: -40°C~+85°C
 STORAGE TEMPERATURE: -40°C~+85°C.
 ELECTRICAL:
 VOLTAGE: 125 VOLTS AC
 CURRENT RATING: 1.5AMP
 DIELECTRIC STRENGTH: 1000 VAC RMS 50HZ OR 60HZ, 1 MIN
 INSULATION RESISTANCE: 500 MEGA OHMS MIN. INITIAL 500V DC FOR 1 MINUTE
 CONTACT RESISTANCE: SINGLE TERMINAL 30 MILLIOHMS MAX. INITIAL 50 MILLIOHMS MAX. AFTER DURABILITY TEST.
 All materials must meet GREENCONN hazardous substances control standards.



Ordering Information

C TZA101 - 16 XX A 001 A X A X

Standard Plating
 02=Gold Flash

Color
 6=Gray

Standard Packing
 B=Tray

格稜股份有限公司
Greenconn Corporation

GENERAL TOLERANCE

X.'±3.0'	X.±0.35
.X'±2.0'	.X±0.30
.XX'±1.5'	.XX±0.25
.XXX'±1.0'	.XXX±0.10

DESIGNED:

DATE:

DWG. NO.

CTZA101-CA1AA

TITLE:

RJ45 8P8C 1*2PORT

CHECKED:

DATE:

PART NO.

CTZA101-16XXA001AXAX

APPROVED:

DATE:

REV. 01

UNIT. mm

SCALE. 1:1

PAGE. 1/1



1

2

3

4

5

6

7

8

9