




FRONT VIEW




RIGHT SIDE VIEW



BOTTOM VIEW



RECOMMENDED PCB LAYOUT
VIEWED FROM COMPONENT SIDE



MATERIAL:
HOUSING: FR52,UL94V-0,BLACK
TERMINAL: PHOSPHOR BRONZE T=0.30MM
6U" GOLD PLATING ON CONTACT AREA.
MACHANICAL:
DURABILITY: 750 CYCLES MIN,12.5MM/MINUTE
INSERTION FORCE: 2.2KG.F MAX
RETENTION STRENGTH: 7.7KG.F BETWEEN JACK
AND PLUG
OPERATING TEMPERATURE: 0°C~+85°C
STORAGE TEMPERATURE: -40°C~+85°C.
ELECTRICAL:
VOLTAGE: 125 VOLTS AC
CURRENT RATING: 1.5AMP
DIELECTRIC STRENGTH: 1000 VAC RMS 50HZ
OR 60HZ, 1 MIN
INSULATION RESISTANCE: 500 MEGA OHMS
MIN. INITIAL 500V DC FOR 1 MINUTE
CONTACT RESISTANCE: SINGLE TERMINAL 30
MILLIOHMS MAX. INITIAL 50 MILLIOHMS MAX.
AFTER DURABILITY TEST.
All materials must meet GREENCONN
hazardous substances control standards.

Ordering Information

C TZD108 - 08 XX A 002 Z X S X

Standard Plating
02=Gold Flash
Selective Plating
05=Gold Flash/Tin
53=Gold 6u"/Tin

Color
1=Black

Standard Packing
B=Tray
Selective Packing
N=PE Bag

格菱股份有限公司
Greenconn Corporation

GENERAL TOLERANCE

X.'±3.0'	X.±0.35
.X'±2.0'	.X±0.30
.XX'±1.5'	.XX±0.25
.XXX'±1.0'	.XXX±0.10

DESIGNED:

DATE:

DWG. NO.

CTZD108-CA2ZS

TITLE.

56 SMT 全塑无灯 (8pin)

CHECKED:

DATE:

PART NO.

CTZD108-08XXA002ZXSX

APPROVED:

DATE:

REV.
A

UNIT.
mm

SCALE.
1:1

PAGE.
1/1



1

2

3

4

5

6

7

8

9