

Specifications:

- 1.1 Current rating: 1 A Max.
rated voltage;5V VDC,
- 1.2 Dielectric withstanding voltage:
500 V(ac) for 1 minute.
- 1.3 Contact resistance: 30mΩ Max.
- 1.4 Insulation resistance: 1000MΩ Min at DC 500V
- 1.5 T0tal mating force: 3.57 Kgf Max.
- 1.6 Total unmating force: 1.02Kgf Min.
- 1.7 Temperature range:0℃~+40℃.
- 1.8 Storage temperature:-40℃~+85℃

6	SHELL-C	BRASS	T=0.30	1
5	SHELL-B	BRASS	T=0.30	1
4	SHELL-A	BRASS	T=0.30	1
3	TERMINAL-B	PHOSPHOR BRONZE	T=0.25	4
2	TERMINAL-A	PHOSPHOR BRONZE	T=0.25	4
1	HOUSING	PBT UL94-V0	—	1
NO.	Name	MATERIAL	THICK	Q' TY

Ordering Information

C UZB278 - 08 XX A 001 A X S X

No.of pins
08

Standard Plating
05=Gold Flash/Tin
Selective Plating
51=Gold 2u"/Tin
58=Gold 30u"/Tin
.....

Color
1=Black
2=White


Standard Packing
B=Tray



Website:www.greenconn.com
E-mail:sales@greenconn.com

REV. A UNIT. mm SCALE. 1:1

3RD.ANG
PROJ.



PAGE. 1/1

GENERAL TOLERANCE

X.'±5.0'	X.±0.30
.X'±3.0'	.X±0.25
.XX'±2.0'	.XX±0.20
.XXX'±1.0'	.XXX±/

DESIGNED:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

DWG. NO.

CUZB278-CA1AS

PART NO.

CUZB278-08XXA001AXSX

TITLE.

USB AF 90度双层半包平弹