


PCB LAYOUT 图仅供参考



Note:

1.Material:

- 1.1 Housing: PA9T UL94V-0
- 1.2 Contact:C5191,t=0.20mm
- 1.3 Shell: Kirsite
- 1.4 O RING(防水圈) : 硅胶(Silica Gel)
- 1.5 waterproof glue(防水胶): 环氧树脂 (Epoxy)
- 1.6 Cap: PA9T
- 1.7 MID PLATE:SUS301

2.ELECTRICAL:

- 2-1:CURRENT RATING: 3.0A
- 2-2:INITIAL CONTACT RESISTANCE :40 MEGOHMS
- 2-3:DIELECTRIC WITHSTANDING VOLTAGE: 100V AC MIN;

3:MECHANICAL CHARACTERISTICS:

- 3-1:MATING FORCE:5~20N
- 3-2:UNMATING FORCE:8~20N(INITIAL), 6~20N(AFTER 10000 CYCLES)
- 3-3:FREQUENCY: 200±50 CYCLES /HOUR,10000 CYCLES
- 3-4:OPERATING TEMPERATURE ;-40°~80°.

4: WATERPROOF: IP-X7.

TABLE:

A5	CC1	B12	GND
A9	VBUS	B9	VBUS
A12	GND	B5	CC2
PIN	SIGNAL NAME	PIN	SIGNAL NAME

Ordering Information

C UZC121 - 06 XX A 001 D X A X


No. of pins 06      Standard Plating 05=Gold Flash/Tin      Color 1=Black 7=Blue      Standard Packing F=CAP+Tape&Reel Selective Plating D=Tape&Reel



Website:www.greenconn.com  
E-mail:sales@greenconn.com

REV. A      UNIT. mm      SCALE. 1:1

3RD.ANG PROJ.



PAGE. 1/2

GENERAL TOLERANCE

X'±5.0'	X.±0.50
.X'±3.0'	.X±0.38
.XX'±2.0'	.XX±0.25
.XXX'±1.0'	.XXX±0.15

DESIGNED:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

DWG. NO.

CUZC121-CA001

PART NO.

CUZC121-06XXA001DXAX

TITLE.

TYPE C 6PIN 直立式 防水型(不带插卡勾)