






N=Number of confacfs



Specifications
 Voltage rating:300VAC
 Current rating: 16 Amps/way max
 Contact resistance: 20mΩ(max)
 Insulation resistance: 5000MΩ/1000V
 Withstanding Voltage:2500VAC(1min) Test time:60sec/1pcs
 Wire range: 12-26AWG
 Mechanical:
 Torque:/
 Operating temperature:-40°C to+105°C
 Materials
 Contact Material:Brass
 Insulator Material: UL 94V-0 PA66
 All materials must meet GREENCONN hazardous substances control standards.

Ordering Information

CXMZ107 - XX XX A 004 E X B X


No.of Pins Per Row 02~24 Standard Plating 01=Tin Color 7=Blue G=Green Standard Packing R=Cartons



Website:www.greenconn.com
 E-mail:sales@greenconn.com

REV. A UNIT. mm SCALE. 1:1

3RD.ANG PROJ.



PAGE. 1/1

GENERAL TOLERANCE

X.±5.0'	X.±0.50
.X'±3.0'	.X±0.30
.XX'±2.0'	.XX±0.20
.XXX'±1.0'	.XXX±/

DESIGNED:

CHECKED:

APPROVED:

DATE:

DATE:

DATE:

DWG. NO.

CXMZ107-CA004EB

PART NO.

CXMZ107-XXXXA004EXBX

TITLE.

Pitch5.08mm-series