



N=Number of contacts

Specifications
 Voltage rating:300VAC
 Current rating:12 Amps/way max
 Contact resistance: 20mΩ(max)
 Insulation resistance: 5000MΩ/1000V
 Withstanding Voltage: 2500VAC(1min)
 Test time:60sec/1pcs
 wire range: 16-24AWG
Mechanical:
 Torque:2.5kgf.cm/M2
 Operating temperature:-40°C to+105°C
Materials
 Contact Material:Brass
 Insulator Material: UL 94V-0 PA66
 All materials must meet GREENCONN hazardous substances control standards.

Ordering Information

C XZZ115 - XX XX A 001 E X Z X

No. of Pins per Row 02~20 Standard Plating 01=Tin

Color 1=Black 7=Blue G=Green Standard Packing R=Carton

Greenconn
 Website:www.greenconn.com
 E-mail:sales@greenconn.com

3RD.ANG PROJ. 	GENERAL TOLERANCE				
	X:±5.0'	X.±0.50			
	.X'±3.0'	.X±0.30			
	.XX'±2.0'	.XX±0.20			
REV. A	UNIT. mm	SCALE. 1:1	PAGE. 1/1	.XXX'±1.0'	.XXX±/

DESIGNED:	DATE:
CHECKED:	DATE:
APPROVED:	DATE:

DWG. NO.
CXZZ115-CA1EZ

PART NO.
CXZZ115-XXXXA001EXZX

TITLE.
pitch 3.5mm-Series