



**Specifications**  
 Voltage rating:300VAC  
 Current rating:12 Amps/way max  
 Contact resistance: 20mΩ(max)  
 Insulation resistance: 5000MΩ/1000V  
 Withstanding Voltage: 2500V AC(1min)Test time:60sec/1pcs  
 Wire range: 16-24AWG  
**Mechanical:**  
 Torque:/  
 Operating temperature:-40°C to +105°C  
**Materials**  
 Contact Material:Brass  
 Insulator Material: UL 94V-0 PA66  
 All materials must meet GREENCONN hazardous substances control standards.

2p fo 6p with wedge,above7p without wedge(including 7p)

N=Number of contacfs

Ordering Information

CXZZ124 - XX XX A 005 E X B X  
 No.of Pins Per Row 02~24      Standard Plating 01=Tin      Color 1=Black 6=Grey 7=Blue G=Green      Standard Packing R=Cartons

Website:www.greenconn.com  
 E-mail:sales@greenconn.com

REV.	UNIT.	SCALE.
A	mm	1:1

3RD.ANG PROJ.  
  
 PAGE. 1/1

GENERAL TOLERANCE	
X.±5.0'	X.±0.50
.X'±3.0'	.X±0.30
.XX'±2.0'	.XX±0.20
.XXX'±1.0'	.XXX±/

DESIGNED:  
 CHECKED:  
 APPROVED:

DATE:  
 DATE:  
 DATE:

DWG. NO.  
 CXZZ124-CA005EB  
 PART NO.  
 CXZZ124-XXXXA005EXBX

TITLE.  
 Pitch3.81m-series