

F

E

D

C

B

A

F




E

D

C

B

A



Specifications

Current Rating:3.0Amp

Insulation Resistance:1000MΩMin.

Dielectric Withstanding Voltage:600VAC

Contact Resistance:20mΩMax.

Operating Temperature:-40°C to +105°C

Materials

Contact Material:

Brass(Pin length less than 25mm)

Phosphor Bronze(The total length of pin is more than 25mm)

Insulator Material:

PBT(Not resistant to high temperature), Nylon(High temperature resistance), LCP(High temperature resistance), UL 94V-0


All materials must meet Greenconn hazardous substances control standards.

No. of PIN/ROW	Dimension Information	
	M	L
02	2.54	5.08
03	5.08	7.62
04	7.62	10.16
05	10.16	12.70
06	12.70	15.24
07	15.24	17.78
08	17.78	20.32
09	20.32	22.86
10	22.86	25.40
11	25.40	27.94
12	27.94	30.48
13	30.48	33.02
14	33.02	35.56
15	35.56	38.10
16	38.10	40.64
17	40.64	43.18
18	43.18	45.72
19	45.72	48.26
20	48.26	50.80
21	50.80	53.34
22	53.34	55.88
23	55.88	58.42
24	58.42	60.96
25	60.96	63.50
26	63.50	66.04
27	66.04	68.58
28	68.58	71.12
29	71.12	73.66
30	73.66	76.20
31	76.20	78.74
32	78.74	81.28
33	81.28	83.82
34	83.82	86.36
35	86.36	88.90
36	88.90	91.44
37	91.44	93.98
38	93.98	96.52
39	96.52	99.06
40	99.06	101.60

Recommended P.C.Board

Layout

(Tolerance:±0.05)



Ordering Information

G PHB210		-	XX	XX	A	XXX	X	1	X	X
Plastic specifications		Water code	No. of Pins per Row 02~40	Positioning column information			Pin length See the drawing	Color 1=Black 2=White 3=Yellow E=Beige	Contact Material A/S/K/T=Phosphor Bronze B/Z/H/W=Brass	Packing code
1=Single row 2=Dual row 3=Tripe row 4=Quadruple				A=No locating post B=Round post C=Square post						
				Plating code 01=Tin 02=Gold Flash 05=Gold Flash/Tin 22=Matte Tin			Insulator Material A=PBT R=Nylon(Halogen Free) C=LCP			

格稜股份有限公司
Greenconn Corporation

GENERAL TOLERANCE

X.°±5.0°	X.±0.30
.X°±3.0°	.X±0.25
.XX°±2.0°	.XX±0.15
.XXX°±1.0°	.XXX±0.10

DWG. NO.

GPHB210-CAXX

PART NO.

GPHB210-XXXX AXXX X1XX

TITLE.

2.54 PIN HEADER DUAL
ROWS R/A TYPE
CONNECTOR

REV.	UNIT.	SCALE.	PAGE.	
01	mm	3:1	1/1	