



Specifications  
 Current Rating:AWG26:1.0Amp  
                   :AWG28:1.0Amp  
                   :AWG30:1.0Amp  
 Voltage Rating: 50V AC/DC.  
 Insulation Resistance:100MΩ Min.  
 Dielectric Withstanding Voltage:500V AC  
 Contact Resistance:30mΩ Max.  
 Operating Temperature:-25°C to +85°C  
 Material: Phosfor bronze alloy.  
 Plating: Nickel underplated all over 50~100u"  
           Bright tin plated 80~160u" over all.  
 Tolerance for all radius is ±0.15mm unless otherwise specified.  
 All materials must meet GREENCONN hazardous substances control standards.

Greenconn's P/N	CABLE SPEC		Diameter of the cable including insulation(mm)
	mm <sup>2</sup>	AWG#	
GRD601-0101AB-R	0.05~0.13	30~26	0.76~1.0

 Website:www.greenconn.com E-mail:sales@greenconn.com	3RD.ANG PROJ.	GENERAL TOLERANCE		DESIGNED:	DATE:	DWG. NO. GRD601-01-R	TITLE. 1.25mm PITCH DISCONNECTABLE CRIMP STYLE CONNECTORS-Terminal		
		X:±3.0'	X:±0.20					CHECKED:	DATE:
		.X'±2.0'	.X±0.15					APPROVED:	DATE:
		.XX'±1.0'	.XX±0.10						
REV. A	UNIT. mm	SCALE. 5:1	PAGE. 1/1			PART NO. GRD601-0101AB-R			