



- 註：(第1、2、3、4項QC需重點檢測)
- 1.材料：C5191R-1/2H T=0.15±0.01mm
 - 2.毛刺：≤0.02mm
 - 3.圖面未特殊要求其公差依圖框左下角公差
 - 4.所有未注圓角：≤0.15mm
 - 5.標示"⊗"為首件與尾件測量部位
 - 6.標示"Ⓜ"為首件與尾件測量部位
 - 7.標示"▽"為首件、尾件與巡檢測量部位
 - 8.所有材料必須滿足GREENCONN有害物質管控標準

 Website: www.greenconn.com E-mail: sales@greenconn.com			3RD.ANG PROJ.	GENERAL TOLERANCE X: ±3.0° X: ±0.15 .X: ±2.0° .X: ±0.10 .XX: ±1.0° .XX: ±0.05 .XXX: ±0.5° .XXX: ±0.03	DESIGNED: CHECKED: APPROVED:	DATE: DATE: DATE:	DWG. NO. GRF159-T2	TITLE. TERMINAL FOR PITCH 2.00mm WIRE TO BOARD CONNECTOR
REV. B	UNIT. mm	SCALE. 5:1	PAGE. 1/1	APPROVED:	DATE:	PART NO. GRF159-0200AD		