

1. Material: Brass.
  2. Plating:  
Nickel underplated all over 100~200u"
  3. Tolerance for all radius is  $\pm 0.15\text{mm}$  unless otherwise specified.
  - ★ 4. All materials must meet GREENCONN hazardous substances control standards.
- "★": Significant Characteristics.  
indicates product characteristics, functionalities, and manufacturing processes regarding to customer's specifications
- "☆": Safety Features  
indicates product characteristics, functionalities, and manufacturing processes complying to legal regulations stated by local government


Greenconn's P/N	CABLE SPEC		Diameter of the cable including insulation(mm)
	mm <sup>2</sup>	AWG#	
GTZ1E2-01S4BL	2.5~0.5	14~20	0.81~1.63



Website: [www.greenconn.com](http://www.greenconn.com)  
E-mail: [sales@greenconn.com](mailto:sales@greenconn.com)

REV. A UNIT. mm SCALE. 4:1

3RD.ANG  
PROJ.



PAGE. 1/1

#### GENERAL TOLERANCE

X.' $\pm 3.0$ '	X. $\pm 0.20$
.X' $\pm 2.0$ '	.X $\pm 0.15$
.XX' $\pm 1.0$ '	.XX $\pm 0.10$
.XXX' $\pm 0.5$ '	.XXX $\pm 0.05$

DESIGNED:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

DWG. NO.

GTZ1E2-01

PART NO.

GTZ1E2-01S4BL

TITLE.

CONTACT PIN SIZE 16