



Specifications
Voltage rating:100V AC/DC
Current Rating:2A AC/DC
Withstanding Voltage:800V AC
Insulation Resistance:1000MΩ Min.
Contact Resistance:20mΩ Max.
After environmental testing: ≤20mΩ
Operating Temperature:−25°C to +85°C
Materials
Insulator Material:PA66 94V-0
All materials must meet GREENCONN
hazardous substances control standards.



3P 示意图



2P 示意图

Ordering Information

GWF181 - XX A XX

No. of Pins
02~16

Materials /Color
M=YN66/White
M1=YN66/Black

Pins	Dimensions(mm)	
	M	L
2	2.00	4.60
3	4.00	6.60
4	6.00	8.60
5	8.00	10.60
6	10.00	12.60
7	12.00	14.60
8	14.00	16.60
9	16.00	18.60
10	18.00	20.60
11	20.00	22.60
12	22.00	24.60
13	24.00	26.60
14	26.00	28.60
15	28.00	30.60
16	30.00	32.60

格菱股份有限公司
Greenconn Corporation

GENERAL TOLERANCE

X:±	X.±
.X'±2.0'	.X±0.30
.XX'±1.0'	.XX±0.20
.XXX'±	.XXX±0.10

DESIGNED:

DATE:

DWG. NO.

GWF181-HA

TITLE.

Pitch 2.0 Housing

CHECKED:

DATE:

PART NO.

GWF181-XXAXX

APPROVED:

DATE:

REV.
A

UNIT.
mm

SCALE.
1:1

PAGE.
1/1



1

2

3

4

5

6

7

8

9