



Specifications
Insulation Resistance: $\geq 1000M\Omega$
Rated Voltage: 250V AC DC
Rated Current: 3.0A AC DC
Withstand Voltage: 800V AC/minute
Contact Resistance: $< 10m\Omega$
Temperature Range: $-40^{\circ}C$ to $+125^{\circ}C$

Mating With:
Wafer: GWFC115
Terminal: GRF174
Optional accessories: GHF631

All materials must meet GREENCONN hazardous substances control standards.

No. of PIN/ROW	Dim M	Dim L	Dim L1	Dim L2
02	2.00	4.40	3.30	
03	4.00	6.40	5.10	
04	6.00	8.40	6.80	
05	8.00	10.40	9.05	
06	10.00	12.40	11.15	10.00
07	12.00	14.40	13.15	10.00
08	14.00	16.40	15.15	10.00
09	16.00	18.40	17.15	12.00
10	18.00	20.40	19.15	17.40
11	20.00	22.40	21.15	17.40
12	22.00	24.40	23.15	17.40
13	24.00	26.40	25.15	17.40
14	26.00	28.40	27.15	17.40
15	28.00	30.40	29.15	17.40

Ordering Information

GHF621 - XX A XX

No. of Pins per Row
02~15

Material/Color
P1=NYLON 66/白色



Website: www.greenconn.com
E-mail: sales@greenconn.com

REV. A UNIT. mm SCALE. 1:1

3RD.ANG PROJ.
PAGE. 1/3

GENERAL TOLERANCE	
X.±5.0'	X.±0.50
.X'±2.0'	.X±0.30
.XX'±1.0'	.XX±0.20
.XXX'±/	.XXX±/

DESIGNED:
CHECKED:
APPROVED:

DATE:
DATE:
DATE:

DWG. NO.
GHF621-HA
PART NO.
GHF621-XXAP1

TITLE.
2.00mm PINCH Housing





