






N=Number of contacts



Specifications
Voltage rating:300VAC
Current rating:16 Amps/way max
Contact resistance: 20mΩ(max)
Insulation resistance: 5000MΩ/1000V
Withstanding Voltage: 2500VAC(1min)
Test time:60sec/1pcs
wire range: 12-26AWG
Mechanical:
Torque:5.0kgf.cm/M3
Operating temperature:-40°C to+105°C
Materials
Contact Material:Brass
Insulator Material: UL 94V-0 PA66
All materials must meet GREENCONN
hazardous substances control standards.

Ordering Information

G XMZ101 - XX XX A 001 E X Z X

No. of Pins per Row
02~24

Standard Plating
01=Tin

Color
1=Black
6=Grey
7=Blue
G=Green
.....

Standard Packing
R=Carton



Website:www.greenconn.com
E-mail:sales@greenconn.com

REV. A UNIT. mm SCALE. 1:1

3RD.ANG
PROJ.
PAGE. 1/1

GENERAL TOLERANCE

X.*±5.0'	X.±0.50
.X'±3.0'	.X±0.30
.XX'±2.0'	.XX±0.20
.XXX'±1.0'	.XXX±/

DESIGNED:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

DWG. NO.

GXMZ101-CA1EZ

PART NO.

GXMZ101-XXXXA001EXZX

TITLE.

Pitch 5.08 Series