


P.C.B LAYOUT



N=Number of contacts

Specifications
 Voltage rating:300VAC
 Current rating:42 Amps/way max
 Contact resistance: 20mΩ(max)
 Insulation resistance: 5000MΩ/1000V
 Withstanding Voltage: 2500VAC(1min)
 Test time:60sec/1pcs
 wire range: /
 Mechanical:
 Torque:/
 Operating temperature:-40°C to+105°C
 Materials
 Contact Material:Brass
 Insulator Material: UL 94V-0 PA66
 All materials must meet GREENCONN
 hazardous substances control standards.

Ordering Information

G XZB109 - XX XX A 001 E X Z X

No. of Pins per Row 02~24 Standard Plating 01=Tin Color 1=Black 6=Grey 7=Blue G=Green Standard Packing R=Carton

 Website:www.greenconn.com E-mail:sales@greenconn.com		3RD.ANG PROJ. PAGE. 1/1	GENERAL TOLERANCE X.'±5.0' X.±0.50 .X'±3.0' .X±0.30 .XX'±2.0' .XX±0.20 .XXX'±1.0' .XXX±/	DESIGNED:	DATE:	DWG. NO. GXZB109-CA001EZ PART NO. GXZB109-XXXX A001EXZX	TITLE. 7.62mm 90°DIP
				CHECKED:	DATE:		
REV. A	UNIT. mm	SCALE. 1:1		APPROVED:	DATE:		