



Technical Specs:
 Insulator:Black glass filled polyester PPS-GF30-FR
 Flammability:UL 94V-0
 Contact:Brass CuZn36Pb3(C36000)
 Rated current:1A
 Contact resistance:max 10 mΩ
 Dielectric strength:min 1,000 V RMS
 All materials must meet GREENCONN
 hazardous substances control standards.

No. of PIN/ROW	M	L
01	0	1.68
02	1.27	2.95
03	2.54	4.22
04	3.81	5.49
05	5.08	6.76
06	6.35	8.03
07	7.62	9.30
08	8.89	10.57
09	10.16	11.84
10	11.43	13.11
11	12.70	14.38
12	13.97	15.65
13	15.24	16.92
14	16.51	18.19
15	17.78	19.46
16	19.05	20.73
17	20.32	22.00
18	21.59	23.27
19	22.86	24.54
20	24.13	25.81
21	25.40	27.08
22	26.67	28.35
23	27.94	29.62
24	29.21	30.89
25	30.48	32.16
26	31.75	33.43
27	33.02	34.70
28	34.29	35.97
29	35.56	37.24
30	36.83	38.51
31	38.10	39.78
32	39.37	41.05
33	40.64	42.32
34	41.91	43.59
35	43.18	44.86
36	44.45	46.13
37	45.72	47.40
38	46.99	48.67
39	48.26	49.94
40	49.53	51.21

Ordering Information

G KEA101 - XX XX A 002 S X B X

No. of Pins per Row 01~40
 Standard Plating 01=TIN, 02=Gold Flash, B1=Gold 3U"
 Color 1=Black
 Standard Packing C=Tube, N=PE Bag



Website:www.greenconn.com
 E-mail:sales@greenconn.com

3RD.ANG PROJ.
 PAGE. 1/1

GENERAL TOLERANCE	
X.*±3.0'	X.±/
.X*±3.0'	.X±0.30
.XX*±3.0'	.XX±0.25
.XXX*±3.0'	.XXX±0.20

DESIGNED:	DATE:
CHECKED:	DATE:
APPROVED:	DATE:

DWG. NO. GKEA101-CA002SB
PART NO. GKEA101-XXXX A002SXBX

TITLE. 1.27mm PIN CONNECTOR H=2.2mm DIP Type
--