



Technical Specs:  
 Insulator:Black glass filled polyester PPS-GF30-FR  
 Flammability:UL 94V-0  
 Contact:Brass CuZn36Pb3(C36000)  
 Rated current:3A  
 Contact resistance:max 10 mΩ  
 Dielectric strength:min 1,000 V RMS  
 All materials must meet GREENCONN  
 hazardous substances control standards.

No. of PIN/ROW	M	L
01	0	2.54
02	2.54	5.08
03	5.08	7.62
04	7.62	10.16
05	10.16	12.70
06	12.70	15.24
07	15.24	17.78
08	17.78	20.32
09	20.32	22.86
10	22.86	25.40
11	25.40	27.94
12	27.94	30.48
13	30.48	33.02
14	33.02	35.56
15	35.56	38.10
16	38.10	40.64
17	40.64	43.18
18	43.18	45.72
19	45.72	48.26
20	48.26	50.80
21	50.80	53.34
22	53.34	55.88
23	55.88	58.42
24	58.42	60.96
25	60.96	63.50
26	63.50	66.04
27	66.04	68.58
28	68.58	71.12
29	71.12	73.66
30	73.66	76.20
31	76.20	78.74
32	78.74	81.28
33	81.28	83.82
34	83.82	86.36
35	86.36	88.90
36	88.90	91.44
37	91.44	93.98
38	93.98	96.52
39	96.52	99.06
40	99.06	101.6

### Ordering Information

G KHB202 - XX XX A 002 S X B X

No. of Pins per Row 01~40  
 Standard Plating 01=TIN, 02=Gold Flash, B1=Gold 3U"  
 Color 1=Black  
 Standard Packing C=Tube, N=PE Bag

 Website:www.greenconn.com E-mail:sales@greenconn.com	3RD.ANG PROJ.  PAGE. 1/1	GENERAL TOLERANCE X.*±3.0' X.±/ .X*±3.0' .X±0.30 .XX*±3.0' .XX±0.25 .XXX*±3.0' .XXX±0.20		<del>DESIGNED: DATE:</del> <del>CHECKED: DATE:</del> <del>APPROVED: DATE:</del>		DWG. NO. GKHB202-CA002SB	TITLE. 2.54 PIN CONNECTOR H=3.00mm DIP
		REV. A UNIT. mm SCALE. 1:1	PART NO. GKHB202-XXXX A002SXBX				